

70D 系列



70^D

BOL
軸承

70°C
耐高溫

7V 5V
12V
複合式電源

產品特色

- 氣壓無油軸承技術，超高壽命、低噪音
- 高達70°C耐高溫工作環境
- 高質感外觀與紮實整體設計
- 配備12V/7V/5V複合式電源轉接線，提供三種轉速選擇

產品規格

70D									
型號	LP70D08R			LP70D09R			LP70D12R		
尺寸 (mm)	80 x 80 x 25			92 x 92 x 25			120 x 120 x 25		
軸承	氣壓無油軸承 (BOL, Barometric Oilless Bearing)								
轉速 (rpm)	2600	1700	1200	2400	1600	1100	1600	1200	900
風量 (CFM)	42.64	29.38	23.27	45.72	32.16	27.00	68.48	51.70	38.83
風量 (m ³ /h)	72.49	49.95	39.56	77.72	54.67	45.90	116.42	87.89	66.01
風壓 (mm-H ₂ O)	3.02	1.50	0.88	2.22	1.42	0.87	1.90	1.26	0.74
噪音 (dBA)	25	21	17	25	20	16	24	20	16
額定電壓 (V)	12	7	5	12	7	5	12	7	5
輸入電流 (A)	0.20	0.12	0.09	0.20	0.14	0.10	0.25	0.15	0.10
輸入電源 (W)	2.4	0.84	0.45	2.40	0.98	0.50	3.00	1.05	0.50
MTBF (小時)	100,000								
接頭	3 Pin								
配件	螺絲*4, 12V/7V/5V複合式轉接線								

